



Cylinder Diameter

Rod Diameterer

The precision : 0.5N, 0.05KG, 0.11lbs /0.001MM ,0.000393inch

[HOME](#) || [COMPANY PROFILE](#) || [PRODUCTS](#) || [SEND INQUIRY](#) || [CONTACT](#)

Compression gas spring

- Parameter D 15 mm / d 6mm
- Parameter D 18 mm / d 8 mm
- Parameter D 22 mm / d 10 mm
- Parameter D 28 mm / d 14 mm
- Picture 01
- Picture 02
- Picture 03
- Picture 04
- Picture 05

- Parameter D 15 mm / d 6mm
- Parameter D 18 mm / d 8 mm
- Parameter D 22 mm / d 10 mm
- Parameter D 28 mm / d 14 mm
- Picture 01
- Picture 02
- Picture 03
- Picture 04
- Picture 05

Locking gas spring

- Parameter of locking gas spring
- Picture of locking gas spring

Sepcial gas spring

- Traction gas spring
- Bidirectional support gas springs
- Three-sect strength value gas spring
- Toolbox gas spring
- Furniture gas spring
- Massage chair and medical equipment angle adjustment
- Machinery gas spring
- Mould gas spring
- Auto chair gas spring
- Car support gas spring
- Hinge buffer gas spring
- Slide buffer

Connector of gas spring

Cabinet gas spring

- Standard cabinet gas spring
- Soft stop cabinet gas spring
- Parameter of cabinet gas spring
- Connector of cabinet gas spring

Ask for gas spring sample

Packing detail

FAQ

- Calcualte the F1 of gas spring
- How to install gas spring

Copy Right **HXL GAS SPRING CO.,LTD.** All Rights Reserved

Add : **Room 504 ,SiMingNan Road No.361-1-2, Xiamen Fujian China,361004**

Tel : (86)592 5611860 . (86)592 5671238 (86)592 5612827 Fax: (86)592 5671238

Email : **sale@gas-springs.cn**